

Highlights

- Ultra Short Throw
- Designed for Education
- Easy Installation & Control
- Easy Maintenance



Projection System	DLP		
Native Resolution	WXGA(1280x800)		
Brightness	2500AL		
Contrast Ratio	5000:1		
Display Color	1.07 Billion Colors		
Lens	F=2.65		
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)		
Throw Ratio	0.36 (96" @ 75cm)		
Image Size (Diagonal)	38"~300"		
Zoom Ratio	Fixed		
Lamp Type	UHP230W		
Lamp (Normal/Economic Mode)*	3500/5000hr		
Keystone Adjustment	1D, Vertical +/- 40 degrees		
Projection Offset	144%+-5%		
Resolution Support	VGA(640 x 480) to UXGA(1600 x 1200)		
Horizontal Frequency	31K~102KHz		
Vertical Scan Rate	23~120Hz		
Compatibility	HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
	Video Compatibility	NTSC, PAL, SECAM	
	3D Compatibility		
Interface	Computer in (D-sub 15pin)	x 2	
	Monitor out (D-sub 15pin)	x 1	
	Composite Video in (RCA)	x 1	
	S-Video in (Mini DIN 4pin)	x 1	
	Component Video in	x 2 (shared with D-sub 15pin)	
	Audio in (Mini Jack)	x 1	
	Audio L/R in (RCA)	x 2	
	Audio out (Mini Jack)	x 1	
	Microphone in (Mini Jack)	x 1	
	Speaker	10W x 2	
	LAN (RJ45)	x 1 (LAN Control)	
	HDMI V1.3	x 1	
	USB (Type Mini B)	x 1 (USB Download & Page up/down)	
	DC 12V Trigger (3.5mm Jack)	x 1	
	RS232 (DB-9pin)	x 1	
Dimensions	Dimensions(W x H x D)	339 x 236.9 x 322.8 mm	
	Weight	5.3kg	
Power	Power Supply	100 to 240 VAC, 50 to 60 Hz	
	Average Power Consumption	SmartEco Mode: 160W	
Audible Noise	34/28 dBA (Normal/Economic mode)		
On-Screen Display Languages	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/Hindi/Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)		
Picture Modes	Dynamic/Presentation/sRGB/Cinema/User 1/User 2		
Accessories	Standard	Optional	
	Remote Control w/ Battery	Presentation Plus	P/N: 65J9306.002
	Power Cord (by region)	Spare Lamp Kit	P/N: 5Jj4V05.001
	User Manual CD	Wireless USB Dongle	P/N: 5Jj0614.A21*
	Quick Start Guide	Wall Mount (T/R 0.3)	P/N:
	Warranty Card (by region)	3D Glasses	P/N: 5Jj0T14.011
	VGA(D-sub 15pin) Cable		

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

*Each region has different wireless dongle P/N, please check PM-BM file for detail.